

STRIP LED



LX-ST-D890-24V-10mm

IP	CRI	DC24V
20/55/65/67/68	>80	



STRIP LED

High cost performance

High density lamp, more uniform light

Self-encapsulated design offers 4 optional 2700-6500K white lights

Mounting : 3M tape

Luminance efficiency Max up to 220LM/W

Ta: -25~40°C ; Tc : 75°C (max)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Max Power	Luminous flux	CCT/K	IP Rating	Dimensions
LX-ST-D890-24V-10mm	4.3W(1m) /17.3W(5m)	4.8W(1m)	845Lm	2700k	IP20/IP55/IP65/IP67	5000*10*1.6mm
			890Lm	3000K		
			925Lm	4000K		
			890Lm	6500K		

Accessories Information

Name	Picture	Code	description
Connector for wire and FPC		LX-94-03-00-0037	10mm width, 2PIN connector of wire and FPC,suitable for white color strip, NO/NA,2PIN wire18- 22AWG
Connector for FPC and FPC		LX-94-42-621020004	10mm width, 2PIN connector of FPC and FPC,suitable for white color strip,NO/NA
Fixed Clip		LX-94-02-00-0018	transparent, 3*8mm self-tapping screws, suitable for 10mm FPC, NO/NA LED strip
Fixed Clip		LX-94-02-00-0016	Fixed clip, transparent, 3*8mm self-tapping screws, suitable for 10mm FPC, SG LED strip
Fixed Clip		LX-94-02-00-0003	Silicone clip, screw: PA 3*8mm, suitable for 10mm FPC,EH/EF/ET strip
Silicone end cap set		LX-94-02-00-0022	Silicone end cap set, including end cap and plug, suitable for 10mm FPC,EH/ET/EF silicone extrusion strip
Mounting groove		LX-94-02-00-0025	Transparent PVC mounting groove,suitable for 10mm FPC,silicone extruded EF/ET strip
Stopper glue		LX-94-16-03010001	Silicone gel, suitable for ST/ET/EH/EF/SF waterproof LED strip

Dimensions

