

STRIP LED

LX-ST-DJ60-24V-8mm



IP 20/55/65	CRI >80	DC24V
-----------------------	-------------------	--------------



STRIP LED

Reel without soldering joint, high cost effective

Max.length : 5000mm(196.85") Cutting unit : 6leds/100mm(3.94")

LED pitch : 16.66mm(0.66")

Min. bend diameter : Φ 60mm(2.36inch) Mounting : 3M tape

Rated current : 0.18A(1m) /0.88A(5m)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Max Power	Luminous flux	CCT/K	IP Rating	Dimensions
LX-ST-DJ60-24V-8mm	4.4W(1m) 22.3W(5m)	4.8W(1m)	450Lm	2700k	IP20/IP55/IP65	5000*8*1.5mm
			480Lm	3000K		
			520Lm	4000K		
			500Lm	6000K		

Accessories Information

Name	Picture	Code	description
Connector for wire and FPC		LX-94-42-620800001	8mm width,IP20-2PIN connector of wire and FPC,suitable for IP20 single color strip,18-22AWG
Connector for FPC and FPC		LX-94-42-620800002	8mm width,IP20-2PIN connector of wire and FPC,suitable for IP20 single color strip.
Connector for wire and FPC		LX-94-03-00-0044	8mm width, 2PIN connector of wire and FPC,suitable for white color and gel coating strip,SG,2PIN wire18-22AWG
Connector for FPC and FPC		LX-94-03-00-0048	8mm width, 2PIN connector of FPC and FPC,suitable for white color and gel coating strip,SG
Fixed Clip		LX-94-02-00-0002	Silicone clip,suitable for 8mm PFC
Fixed Clip		LX-94-02-00-0015	Fixed clip, transparent, 3*8mm self-tapping screws,suitable for 8mm FPC,SG LED strip
Fixed Clip		LX-94-02-00-0017	Fixed clip,8mm FPC.IP20,transparent, 3*8mm self-tapping screws
Hole plug		LX-94-02-00-0021	Silicone end cap without hole,suitable for 8mm PFC, IP65 IP67 waterproof LED strip
Mounting groove		LX-94-02-00-0024	Transparent PVC mounting groove,suitable for 8mm FPC,silicone extruded EF/ET strip
Stopper glue		LX-94-16-03010001	Silicone gel,suitable for IP65 and IP67 LED strip

Dimensions

