


DOWNLIGHT

MAGNETIC SPOTLIGHT RS



MAGNETIC SPOTLIGHT R/S

Magnetic suction installation. The grille design of completely hidden lamp makes the light softer, so you will feel more comfortable in the space.

Tunable White allows the colour temperature to be continuously adjusted from warm light to cool light.

Applications : Showrooms, Restaurants, Star-rated Hotels, Villas, Residential buildings, etc.

Physical : Aluminum

Colour(housing) : black

Colour(reflector) : Black

Colour temperature : 2700K, 3000K, 4000K, 5000K



References

Reference	Led Power	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions				
LX-DL-G201 / LX-DL-G203	1W	47-72lm	2700K	15°/24°/33°	IP20	(20*20*45mm)/ (250*24*37mm)				
		48-78lm	3000K			(Ø20*45mm)/ (250*24*37mm)				
	3W	79-124lm	2700K			(20*20*45mm)/ (250*24*37mm)				
		82-134lm	3000K			(Ø20*45mm)/ (250*24*37mm)				
LX-DL-G202 / LX-DL-G204	2*1W	94-144lm	2700K			15°/24°/33°	IP20	(20*20*45mm)/ (250*24*37mm)		
		96-156lm	3000K					(Ø20*45mm)/ (250*24*37mm)		
	2*3W	158-248lm	2700K					(20*20*45mm)/ (250*24*37mm)		
		164-268lm	3000K					(Ø20*45mm)/ (250*24*37mm)		
LX-DL-G205 / LX-DL-G206	3*1W	141-216lm	2700K					15°/24°/33°	IP20	(20*20*45mm)/ (250*24*37mm)
		144-234lm	3000K							(Ø20*45mm)/ (250*24*37mm)
	3*3W	237-372lm	2700K							(20*20*45mm)/ (250*24*37mm)
		246-402lm	3000K							(Ø20*45mm)/ (250*24*37mm)

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Features



Dimensions

