

MAGNETIC TRACK LIGHT



LX-DL-M20GW

IP 20	CRI >90	SDCM <3 Step	DC48V
-----------------	-------------------	------------------------	--------------

		CASAMBI
---	--	----------------

	CE	RoHS	50000h
---	-----------	-------------	---------------

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- Length: 600mm/1000mm/1200mm optional
- CCT: 2700/3000/3500/4000K optional
- Light efficiency: 90 lm/W
- Lighting direction: downward
- Application: Indoor



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Input Voltage	Type Power	Max Power	Luminous flux	CRI	CCT/K	Beam Angle	IP Rating	Length
LX-DL-M20GW	48VDC	10W	11W	820lm	>90	2700K	60°x25° x75°	IP20	600mm
				840lm		3000K			
				860lm		3500K			
				900lm		4000K			
		15W	16.5W	1235lm		2700K			1000mm
				1255lm		3000K			
				1290lm		3500K			
				1350lm		4000K			
		20W	22W	1645lm		2700K			1200mm
				1675lm		3000K			
				1720lm		3500K			
				1800lm		4000K			

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

Dimensions

