

MAGNETIC TRACK LIGHT



LX-DL-M20I-50

| | | | |
|-----------------|-------------------|------------------------|--------------|
| IP 20 | CRI >90 | SDCM <3 Step | DC48V |
|-----------------|-------------------|------------------------|--------------|

| | | |
|--|--|----------------|
| | | CASAMBI |
|--|--|----------------|

| | | | |
|--|-----------|-------------|---------------|
| | CE | RoHS | 50000h |
|--|-----------|-------------|---------------|

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- CCT: 2700/3000/3500/4000K optional
- Light efficiency: 66 lm/W
- Lighting direction: downward
- Application: Indoor



luxio
L I G H T I N G

www.luxio-lighting.com

References

| Reference | Input Voltage | Type Power | Max Power | Luminous flux | CRI | CCT/K | Beam Angle | IP Rating | Length |
|---------------|---------------|------------|-----------|---------------|-----|-------|------------|-----------|--------|
| LX-DL-M20I-50 | 48VDC | 5W | 5.5W | 300lm | >90 | 2700K | 24° | IP20 | 1300mm |
| | | | | 310lm | | 3000K | | | |
| | | | | 320lm | | 3500K | | | |
| | | | | 330lm | | 4000K | | | |
| | | | | 300lm | | 36° | 2700K | | |
| | | | | 310lm | | | 3000K | | |
| | | | | 320lm | | | 3500K | | |
| | | | | 330lm | | | 4000K | | |

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

Dimensions

