

MAGNETIC TRACK LIGHT



LX-DL-M20LA

| | | | |
|----|-----|---------|-------|
| IP | CRI | SDCM | DC48V |
| 20 | >90 | <3 Step | |

| | | |
|---|------|---------|
| 2 | tuya | CASAMBI |
|---|------|---------|

| | | | |
|---|----|------|--------|
| 3 | CE | RoHS | 50000h |
|---|----|------|--------|

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- Length: 300mm/600mm/900mm optional
- CCT: 2700/3000/3500/4000K optional
- Light efficiency: 100 lm/W
- Lighting direction: downward
- Application: Indoor



luxio
L I G H T I N G

www.luxio-lighting.com

References

| Reference | Input Voltage | Type Power | Max Power | Luminous flux | CRI | CCT/K | Beam Angle | IP Rating | Length |
|-------------|---------------|------------|-----------|---------------|-----|-------|-----------------|-----------|--------|
| LX-DL-M20LA | 48VDC | 7W | 7.7W | 640lm | >90 | 2700K | 90°x45° x15° | IP20 | 300mm |
| | | | | 650lm | | 3000K | | | |
| | | | | 670lm | | 3500K | | | |
| | | | | 700lm | | 4000K | | | |
| | | 14W | 15.4W | 1280lm | | 2700K | | | 600mm |
| | | | | 1305lm | | 3000K | | | |
| | | | | 1340lm | | 3500K | | | |
| | | | | 1400lm | | 4000K | | | |
| | | 20W | 22W | 1830lm | | 2700K | | | 900mm |
| | | | | 1860lm | | 3000K | | | |
| | | | | 1915lm | | 3500K | | | |
| | | | | 2000lm | | 4000K | | | |

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

Dimensions

