

MAGNETIC TRACK LIGHT



LX-DL-M20LS

IP 20	CRI >90	SDCM <3 Step	DC48V
-----------------	-------------------	------------------------	--------------

		CASAMBI
---	--	----------------

	CE	RoHS	50000h
---	-----------	-------------	---------------

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- Length: 300mm/600mm/900mm optional
- CCT: 2700/3000/3500/4000K optional
- Light efficiency: 100 lm/W
- Lighting direction: downward
- Application: Indoor



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Input Voltage	Type Power	Max Power	Luminous flux	CRI	CCT/K	Beam Angle	IP Rating	Length
LX-DL-M20LS	48VDC	7W	7.7W	640lm	>90	2700K	100°x 90°x15°	IP20	300mm
				650lm		3000K			
				670lm		3500K			
				700lm		4000K			
		14W	15.4W	1280lm		2700K			600mm
				1305lm		3000K			
				1340lm		3500K			
				1400lm		4000K			
		20W	22W	1830lm		2700K			900mm
				1860lm		3000K			
				1915lm		3500K			
				2000lm		4000K			

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

Dimensions

