

MAGNETIC TRACK LIGHT



LX-DL-M20SZ-65

| | | | |
|----|-----|---------|-------|
| IP | CRI | SDCM | DC48V |
| 20 | >90 | <3 Step | |

| | | |
|--|--|---------|
| | | CASAMBI |
|--|--|---------|

| | | | |
|--|----|------|--------|
| | CE | RoHS | 50000h |
|--|----|------|--------|

- Material : AL6063-T5, spraying surface
- Coating : Black (RAL9005)
- Size: Ø30mm optional
- CCT: 2700/3000/3500/4000K optional
- Light efficiency: 59 lm/W
- Application: Indoor



luxio
L I G H T I N G

www.luxio-lighting.com

References

| Reference | Input Voltage | Type Power | Max Power | Luminous flux | CRI | CCT/K | Beam Angle | IP Rating | Size |
|----------------|---------------|------------|-----------|---------------|-----|-------|------------|-----------|------|
| LX-DL-M20SZ-65 | 48VDC | 12W | 13.2W | 640lm | >90 | 2700K | 15°-36° | IP20 | 65mm |
| | | | | 660lm | | 3000K | | | |
| | | | | 680lm | | 3500K | | | |
| | | | | 700lm | | 4000K | | | |

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

Dimensions

