

PROFIL LIGHT



LX-PL-LE2711

24V	CRI >80/95	PF >0.9	IK 10	IP 65
-----	---------------	------------	----------	----------



LX-PL-LE2711




- Applied to the floor, integrated with architecture
- Very thin design, suitable for indoor floor, outline & decorating
- AL6063-T5 aluminum profile with high-quality surface treatment.
- Close-fitting design without screw, Make installation more convenient.





luxio
L I G H T I N G

www.luxio-lighting.com

Standard Configuration

Picture	Item	Parameter	Model
	Profile	Profile weight : 0.76kg/2.5m Size : L2500*W27*H11mm Material : AL6063-T5 Surface processing : Anodizing	/
	Cover	Type: Frosted diffuser Material : PC Light transmittance : 75% Size : L2500*W18*H3.4mm PC Feature : The diffuser will extend (shrink) 0.8mm/m when the temperature rises (drops) 10°C.	/
	End caps	Size : L27*W11*H7.8mm Material : PC	LX-EC-LE2711

Optional Accessories

Picture	Item	Parameter	Model
	Flexible strip	Material : FPC,CCT:1900/2300/2700/3000/3500/4000/5000/6000K ; CRI>90/>95 ; Voltage : 24V ; Power : 16.2W/m ; Lumen : 1860Lm/m ; Width : 10mm ; Minimum cutting unit : 7LEDs/42mm ;	LX-ST-D8168-24V-10mm
	End caps with hole	Size : L27*W11*H7.8mm Material : PC	LX-EC-LE2711

Fixings



Dimensions

