

PROFIL LIGHT



LX-PL-LG7043

24V	CRI >80/95	PF >0.9	IP 20
-----	---------------	------------	----------



LX-PL-LG7043




- Apply to gypsum lines, integrated into architecture.
- Arc cover design, wider luminous surface.
- Detachable clasp design, easy to install
- AL6063-T5 aluminum profile with high-quality surface treatment.





luxio
L I G H T I N G

www.luxio-lighting.com

Standard Configuration

Picture	Item	Parameter	Model
	Profile and pendant	Profile weight: 1.63kg/2.5m Pendant weight: 0.53kg/2.5m Profile Size: L2500*W41.6*H70mm Pendant Size: L2500*W7.5*H43.5mm Material: AL6063-T5 Surface processing: Anodizing	/
	Cover	Type: Frosted diffuser Material: PC Light transmittance: 70% Size: L2500*W18.9*H6.5mm PC Feature: The diffuser will extend (shrink) 0.8mm/m when the temperature rises (drops) 10°C.	/
	End caps	Size: L70*W43*H2mm Material: AL	LX-EC-LG7043

Optional Accessories

Picture	Item	Parameter	Model
	Flexible strip LX-ST-D6140-24V-8mm	Material: FPC, CCT: 2700/3000/4000/6000K; Ra > 90; Voltage: 24V; Power: 6.6W/m; Lumen: 710Lm/m; PCB width: 8mm; Minimum cut: 50mm;	LX-ST-D6140-24V-8mm
	Screw	Size: M3.5*40mm Material: Carbon steel	LX-CL-01

Dimensions

