

PROFIL LIGHT



LX-PL-LR3840(B)

24V	CRI >80/95	PF >0.9	IP 20
-----	---------------	------------	----------



LX-PL-LR3840(B)




- Rimless recessed design, integrated into architecture.
- AL6063-T5 aluminum profile with high-quality surface treatment.
- Close-fitting end cap design without screw, make installation more convenient.





luxio
L I G H T I N G

www.luxio-lighting.com

Standard Configuration

Picture	Item	Parameter	Model
	Profile	Profile weight: 1.75kg/2.5m Size: L2500*W73.3*H40mm Material: AL6063-T5 Surface processing: Spraying RAL9003	/
	Cover	Type: Frosted diffuse Material: PC Light transmittance: 60% Size: L2500*W13.5*H8.5mm (shrink) 0.8mm/m when the temperature rises (drops) 10°C.	/
	End caps	Size: L43.3*W40*H1.5mm Material: AL6063-T5	LX-EC-LR3840(B)

Optional Accessories

Picture	Item	Parameter	Model
	Flexible strip LX-ST-D6280-24V -8mm	Material: FPC, CCT: 2700/3000/4000/6000K; Ra > 90; Voltage: 24V; Power: 15W/m; Lumen: 1650Lm/m; PCB width: 8mm; Minimum cut: 7LED/25mm;	LX-ST-D6280-24V -8mm
	Screw	Size: M3.5*40mm Material: Carbon steel	LX-CL-01

Dimensions

