


STRIP LED



LX-ST-DF7-24V-4mm

IP 20/65	CRI >90	DC24V
--------------------	-------------------	--------------



- Light line and dot-free with big emitting angle
- CRI>90,85LM/W@4000K
- suit for furniture lighting and decorative lighting application
- 7 optional 2700K/3000K/4000K/6500K/R/G/B
- Rated current : 0.375A(1m) 0.79A(2.5m)
- On-off times: 10000 (test times)
- Max.length : 2500mm(8.2')
- Cutting unit : 8leds/50mm(1.97")
- Min. bend diameter : Φ 60mm(2.36")
- Mounting : 3M tape
- Copper foil: 2oz



luxio
L I G H T I N G


www.luxio-lighting.com

References

Reference	Typical Power	Max Power	Luminous flux/m	CRI	CCT/K	IP Rating	Dimensions
LX-ST-DF7-24V-4mm	9W/(1m) & 19W/(2.5m)	10W(1m)	610lm	Ra>90	2700K	IP20/IP65	2500*4*1.6mm
			680lm		3000K		
			760lm		4000K		
			810lm		6500K		
			/		R 620-630nm		
			/		G 520-530nm		
			/		B 450-460nm		

- 1.The tolerance of output data can be vary up to 15%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/1merter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.

Dimensions



Electronic & output data

IP Process	Picture	Picture description	Size	Optional CCT/color for finished product	Lumen output rate
NO	 NO/IP20	No proof	4mm*1.6mm	2700K/3000K/4000K/6500K/R/G/B	100%
NANO	 NANO/IP65	Nano-proof	4mm*1.6mm	2700K/3000K/4000K/6500K/R/G/B	98%

Precautions

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -250°C~400°C
- Storage temperature: 0°C~600°C. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.