

GARDEN LIGHT



BET

IP 66	IK 08	PF 0.95	CRI >70/>80	AC220-240V
-----------------	-----------------	-------------------	-----------------------	------------



Garden Light

Body : Aluminum Body

Surface : Electrostatic powder paint

Connectors : Stainless steel (304grade)

Gasket : EPDM Gasket (Hardness value A 20-25)

Wind trap area : 0.9m²

LED module : Very powerful LEDs integrated on the PCB

Drive surge protection : 0/618/6kV

Serial wiring : lo entr Single cable entry



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Input Voltage	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-G-BET	5W	AC220-240V	3000K : 600lm 4000K : 650lm	3000K/4000K /5000K	—	IP66	(H300/H800mm)*(Ø120/Ø125mm)
	7W		3000K : 840lm 4000K : 900lm				(H400/H1000mm)*(Ø120/Ø125mm)
	9W		3000K : 1000lm 4000K : 1180lm				(H500/H1500mm)*(Ø125/Ø150mm)

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Mounting hole

