

# DOWNLIGHT

## GARON W



<b>IP</b>	<b>IK</b>	<b>PF</b>	<b>CRI</b>	<b>UGR</b>	<b>SDCMS3</b>	<b>CLASS II</b>
20	03	0.9	>90	>19		

Optional

 1-10V		ON/OFF	AC220-240V
---	---	--------	------------

 5		TRIDONIC		RoHS	50000h@L80
---	---	----------	---	------	------------

### GARON W

Installation : recessed

Driver : remote

Adjustability : tilt 30 degrees

Fixture material housing : die-cast aluminum

Standard finish : white / black

reflector : White / Black

Optional accessories : trimless mounted kit

Environmental temp : -20°C / +40°C

System efficacy (3000K CRI 90) : 60LM/W

Frequency : 50/60 Hz



## References

Reference	Led Power	System Power	Luminous flux	CCT/K	OPTICS	IP Rating	Cut-out size	Dimensions
LX-DL-S325	2x 21.6W	2x24W	1440lmx2	2700K/3000K/ 4000K	15°/24°/38°/ 50°/60°	IP20	L209 x W97mm	L207.4 x W93.4 x H139mm
	2x25.2W	2x28W	1680lmx2					

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

## Dimensions

